



AXQJ, IFSI AI, AXCMK-HF

XLPE insulated and HFFR sheathed power cable with Cu concentric cond.,
 rated voltage 0,6/1

APPLICATION

Power cable designed for fixed installation in dry and damp environment, suitable for mounting on or under plaster, on cable trays, and embedded in walls or concrete. Not intended for direct laying in ground or water. For outdoor use, the cable may be installed in conduits, provided that adequate measures are taken to prevent water ingress. Suitable for supply systems in an emergency. Appropriate for application in all situations where people and property need to be protected in case of fire. Recommended for public utility buildings with a high concentration of people such as: hotels, shopping malls, hospitals, schools, airports, underground railways, etc. and for industrial complex like power plants, transformers stations. Concentric conductor serves as electromagnetic screen, which could also be applied as neutral conductor

CONSTRUCTION

Conductors: Al, class 2 according to EN 60228
 Insulation: XLPE compound
 Bedding: Extruded elastomere or plastomere compound or plastic tape
 Concentric conductor: Cu wires with counter helix of Cu tape
 Sheath: HFFR compound

CORE IDENTIFICATION

According to HD 308 S2

Insulation Color:

3-core (b): ● Black ● Brown ● Grey

4-core (b): ● Blue ● Brown ● Black ● Grey

Outer Sheath Colour:

● Black

Other colours available on request

TECHNICAL CHARACTERISTICS

CPR class: Dca – s1,d2,a1

Test voltage: 4 kV AC, 50 Hz, 5 min. per core

Rated voltage: 0,6/1 kV

Min. laying temperature: -15°C

Min. working temperature: -40°C

Max. cond. operating temp.: 90°C

Max. short-circuit temperature: 250°C

Bending radius (min): single-core- 20D;
 multicore- 16D, D – overall diameter

Min. bending radius during installation:
 single-core- 10D; multicore- 8D

Fire properties: IEC 60332-1-2; IEC 60332-3-24
 IEC 61034-2; IEC 60754-1
 IEC 60754-2

STANDARD

SFS 5546; HD 604 S1, P. 5I; SS 424 14 18;
 IEC 60502-1

CERTIFICATION



NOMINAL CROSS-SECTION	MAX. RESISTANCE AT 20°C	CURRENT CAPACITY IN AIR		CURRENT CAPACITY IN GROUND	SHORT CIRCUIT CURRENT, 1 S	OUTER DIAM. (APPROX.)	CABLE WEIGHT (APPROX.)
		METHOD A *	METHOD C **				
mm ²	Ω/km	A	A	A		mm	kg/km
3x25/16	1,200/1,830	72	102	130	2,34	23,4	591
3x35/16	0,868/1,830	88	126	160	3,27	25,8	707
3x50/16	0,641/1,200	105	153	190	4,67	27,8	852
3x70/21	0,443/0,868	133	195	240	6,54	30	1162
3x95/29	0,320/0,641	159	236	285	8,88	33,1	1508
3x120/41	0,253/0,443	185	274	325	11,22	36,4	1918
3x150/41	0,206/0,443	208	317	370	14,02	40,3	2254
3x185/57	0,164/0,320	236	361	420	17,29	44,5	2840
3x240/72	0,125/0,253	278	427	480	22,43	50,1	2610
3x300/88	0,100/0,206	316	492	550	28,04	54,7	4404
4x16/10	1,910/1,830	55	80	100	1,5	21,3	495
4x25/16	1,200/1,830	72	102	130	2,34	25,4	665
4x35/16	0,868/1,830	88	126	160	3,27	25,9	802
4x50/16	0,641/1,200	105	153	190	4,67	29,1	1092
4x70/21	0,443/0,868	133	195	240	6,54	33,7	1445
4x95/29	0,320/0,641	159	236	285	8,88	37,5	1989
4x120/41	0,253/0,443	185	274	325	11,22	41,4	2383
4x150/41	0,206/0,443	208	317	370	14,02	45,7	2838
4x185/57	0,164/0,320	236	361	420	17,29	50,1	3532
4x240/72	0,125/0,253	278	427	480	22,43	56,5	4697
4x300/88	0,100/0,206	316	492	550	28,04	61,7	5518

Basic assumptions in ground installations are:

- temperature of ground: +15°C
- depth of laying: 0,7 m
- thermal resistivity of soil: 0,7 K m/W

In air installations the ambient is +25°C

*Method A of installation: a cable in conduit in a thermal insulated wall (see reference method A2 in IEC 60364-5-52)

**Method C of installation: a cable on a wooden wall (see reference method C in IEC 60364-5-52)