



BFSI / FRHF

Power cable 0,6/1 kV halogen – free, low smoke fire resistant cable with Cu conductors

APPLICATION

Fire resistant security cables for installation in locations with high safety requirements, such as industrial complexes, power stations, public buildings, hotels, underground railway systems, hospitals etc. Installations in the open air, underground, indoors, in cable ducts. Not suitable for use in water. Cables may be laid directly in ground if installed properly and carefully acc. to REN leaf 9000 guide. Expected lifetime 50 years, provided proper installation, load and ambient temperature.

CONSTRUCTION

Conductors: Cu, class 2 according to EN 60228

Primary insulation: mica tape

Insulation: XLPE compound

Bedding: Extruded halogen-free compound or plastic halogen-free tape

Concentric conductor: Copper wires and copper tape helically (spirally) applied

Sheath: HFFR compound, UV resistant

CORE IDENTIFICATION

According to HD 308 S2

Insulation Color:

2-core: ●Brown ●Blue

3-core (a): ●Green/Yellow ●Brown ●Blue

3-core (b): ●Black ●Brown ●Grey

4-core (a): ●Green/Yellow ●Brown ●Black ●Grey

4-core (b): ●Blue ●Brown ●Black ●Grey

5-core: ●Green/Yellow ●Blue ●Brown ●Black ●Grey

Outer Sheath Colour:

●Orange

Other colours available on request

TECHNICAL CHARACTERISTICS

Test voltage: 4 kV, AC, 50 Hz, 5 min. per core

Rated voltage: 0,6/1 kV

Bending radius (min): single-core- 15D;
multicore- 12D

Lowest temp. For fixed installation: -40°C

Min. laying temperature: -20°C

Max. working temperature: 90°C

Max. short-circuit temperature: 250°C

Circuit integrity (E90): DIN 4102-12

Low smoke emitting: EN 61034-2

Halogen free: EN 60754-1; EN 60754-2,
0,5% HCl innhold

Vertical flame spread: EN IEC 60332-3-24

Flame propagation: EN 60332-1-2

Circuit integrity: IEC 60331-21, IEC 60331-1,
IEC 60331-2, IEC 60331-11, IEC 60331-25

CERTIFICATION



International
Electrotechnical
Commission



STANDARDS

HD 604 5D, IEC 60502-1

NOMINAL CROSS-SECTION	CONDUCTOR SHAPE	MAX. RESISTANCE AT 20°C	CURRENT CAPACITY IN AIR	OUTER DIAM. (APPROX.)	CABLE WEIGHT (APPROX.)
mm ²		Ω/km	A	mm	kg/km
2x1,5/1,5	RE	12,1/12,1	25	14,2	196
2x2,5/2,5	RE	7,41/7,41	33	15	225
2x4/4	RE	4,61/4,61	43	16,3	285
2x6/6	RE	3,08/3,08	54	17,6	353
2x10/10	RE	1,83/1,83	75	19,3	486
2x16/16	RE	1,15/1,15	100	21,1	670
2x25/16	RM	0,727/1,15	136	25,9	943
2x35/16	RM	0,524/1,15	165	28	1155
3x1,5/1,5	RE	12,1/12,1	25	14,8	222
3x2,5/2,5	RE	7,41/7,41	33	15,6	260
3x4/4	RE	4,61/4,61	43	17	335
3x4/4	RM	4,61/4,61	43	17,7	347
3x6/6	RE	3,08/3,08	54	18,4	422
3x6/6	RM	3,08/3,08	54	18,8	431
3x10/10	RE	1,83/1,83	75	20,2	591
3x10/10	RM	1,83/1,83	75	20,8	604
3x16/16	RE	1,15/1,15	100	22,1	828
3x16/16	RM	1,15/1,15	100	23	851
3x25/16	RM	0,727/1,15	136	27,3	1196
3x35/16	RM	0,524/1,15	165	29,6	1497
3x50/25	SM	0,387/0,727	201	29,7	1896
3x70/35	SM	0,268/0,524	255	33,6	2645
3x95/50	SM	0,193/0,387	314	36,7	3547
3x120/70	SM	0,153/0,268	364	40,5	4488
3x150/70	SM	0,124/0,268	416	44,7	5373
3x185/95	SM	0,0991/0,193	480	48,6	6705
3x240/120	SM	0,0754/0,153	565	54,6	8690

NOMINAL CROSS-SECTION	CONDUCTOR SHAPE	MAX. RESISTANCE AT 20°C	CURRENT CAPACITY IN AIR	OUTER DIAM. (APPROX.)	CABLE WEIGHT (APPROX.)
mm ²		Ω/km	A	mm	kg/km
4x1,5/1,5	RE	12,1/12,1	25	15,8	247
4x2,5/2,5	RE	7,41/7,41	33	16,7	294
4x4/4	RE	4,61/4,61	43	18,2	382
4x6/6	RE	3,08/3,08	54	19,7	486
4x6/6	RM	3,08/3,08	54	20,7	495
4x10/10	RE	1,83/1,83	75	21,7	690
4x10/10	RM	1,83/1,83	75	22,4	705
4x16/16	RE	1,15/1,15	100	23,9	977
4x16/16	RM	1,15/1,15	100	24,9	1002
4x25/16	RM	0,727/1,15	136	29,7	1429
4x35/16	RM	0,524/1,15	165	32,2	1821
4x35/16	SM	0,524/1,15	165	29,8	1810
4x50/25	SM	0,387/0,727	201	33,2	2419
4x70/35	SM	0,268/0,524	255	37,6	3375
4x95/50	SM	0,193/0,387	314	41,3	4533
4x120/70	SM	0,153/0,268	364	46,1	5742
4x150/70	SM	0,124/0,268	416	50,1	6874
4x185/95	SM	0,0991/0,193	480	54,8	8594
4x240/120	SM	0,0754/0,153	565	61,4	11135
5x1,5/1,5	RE	12,1/12,1	25	16,8	284
5x2,5/2,5	RE	7,41/7,41	33	17,9	344
5x4/4	RE	4,61/4,61	43	19,5	449
5x6/6	RE	3,08/3,08	54	21,1	574
5x10/10	RE	1,83/1,83	75	23,4	820
5x16/16	RE	1,15/1,15	100	25,8	1167
3x185/95	SM	0,0991/0,193	480	48,6	6705
3x240/120	SM	0,0754/0,153	565	54,6	8690